箱式电阻回火炉_Chamber Style Tempering Furnace



| 优点 | • 可程序式温度设定 | |
|------|-----------------|--|
| | • 自动警报和数据记录 | |
| 温度范围 | 650~800 (°C) | |
| 使用于 | • 供金属工件热处理,也可用于 | |
| | 化工行业的催化剂焙烧 | |

| 型号 | 有效尺寸 | 电压/功率 | |
|----------|-------------|--------|--|
| | (mm)(W×L×H) | (Kw/V) | |
| CSTF-980 | 980×780×460 | 30/380 | |
| CSTF -C | 依照需求客制化 | | |

箱式电阻回火炉_Chamber Style Tempering Furnace



| Advantage | Programmable temperature setting Auto alarm with data recording device |
|----------------------|---|
| Temperature Range | 650~ 800 (℃) |
| Application | Can be use in metal's heat treatment, and catalyzer calcinations for Chemical Industry |

| Туре | Work | Voltage/Power | |
|----------|-------------------------|---------------|--|
| | Dimension | (Kw/V) | |
| | (mm)(W×L×H) | | |
| CSTF-980 | 980×780×460 | 30/380 | |
| CSTF -C | Customized upon request | | |

水洗真空清洗机 Vacuum Water Cleaner



| Advantage | Vacuum heating design plus |
|-------------|--|
| | cleaning mechanism |
| | Can use alkaline solution or |
| | other non corrosive solution |
| | for cleaning |
| | Include alkaline solution tank |
| | and clean water tank |
| Application | Cleaning with Vacuum process |
| | and solution |

| Туре | Work | Cleaning | |
|----------|-------------------|----------|--|
| | Dimension | Load | |
| | (mm)(W×L×H) | (Kg) | |
| VWC-200 | 380×760×350 | 200 | |
| VWC-400 | 600×900×600 | 400 | |
| VWC-600 | 600×1200×600 | 600 | |
| VWC-1000 | 760×1200×800 | 1000 | |
| VWC -C | Customized Custor | | |
| | upon request | upon | |
| | | request | |

