

## 升降式高温炉 Elevator High Temperature Furnace



加热方式	<ul style="list-style-type: none"> <li>☑ 电加热 (热风循环)</li> <li>☑ 燃气加热</li> <li>☑ 石墨加热</li> </ul>
优点	<ul style="list-style-type: none"> <li>☑ 均温度优良 (<math>\pm 5^{\circ}\text{C}</math>)</li> <li>☑ 在加热室能自动控温和显示氧含量</li> <li>☑ 可依客户需求, 提供炉内不同的充入气体和环境</li> <li>☑ 特殊保温节省能源消耗</li> <li>☑ 提供高纯度的气体环境, 并减少气体消耗</li> </ul>
使用于	<ul style="list-style-type: none"> <li>☑ 还原</li> <li>☑ 段烧/焙烧</li> <li>☑ 烧结</li> <li>☑ 涂料</li> </ul>

型号	尺寸(mm) (W×L×H)	温度范围 ( $^{\circ}\text{C}$ )
EF-01	500×500×500	100~1200
EF-02	800×800×800	100~1200
EF-03	1000×1000×1000	100~1200
EF-04	1500×1500×1500	100~1200
EF-05	2000×2000×2000	100~1200
EF-C	依照需求客制化尺寸	100~1200

## 升降式高温炉 Elevator High Temperature Furnace



Heating Method	<ul style="list-style-type: none"> <li>☞ Electric Heating (convection)</li> <li>☞ Gas Heating</li> <li>☞ Graphite Heating (in higher temperature)</li> </ul>
Advantage	<ul style="list-style-type: none"> <li>☞ Temperature Uniformity (<math>\pm 5^{\circ}\text{C}</math>)</li> <li>☞ Automatic temperature control and oxygen content in the chamber</li> <li>☞ Accommodate reactive or inert gas atmospheres upon customer's request</li> <li>☞ Energy efficient design insulation</li> <li>☞ Ultra-pure atmospheric environment with minimal gas consumption</li> </ul>
Application	<ul style="list-style-type: none"> <li>☞ Reduction</li> <li>☞ Calcination</li> <li>☞ Sintering</li> <li>☞ Coating Application</li> </ul>

Type	Dimension(mm) (W×L×H)	Temperature Range ( $^{\circ}\text{C}$ )
EF-01	500×500×500	100~1200
EF-02	800×800×800	100~1200
EF-03	1000×1000×1000	100~1200
EF-04	1500×1500×1500	100~1200
EF-05	2000×2000×2000	100~1200
EF-C	Customized upon request	100~1200